

Contactor, Size 00, 3-pole, AC-3 4 kW/400 V, screw terminal
Auxiliary switch 10E (1 NO) 24 V DC DC operation



Figure similar

Product designation	Miniature contactor
Product type designation	3TF2
General technical data	
Size of contactor	0
Protection class IP	
• on the front	IP20
Reference code acc. to DIN EN 81346-2	Q
Ambient conditions	
Ambient temperature	
• during operation	-25 ... +55 °C
Main circuit	
Number of poles for main current circuit	3
Number of NO contacts for main contacts	3
Number of NC contacts for main contacts	0
Operating current	
• at AC-3	

— at 400 V rated value • at AC-4 at 400 V rated value	9 A 2.6 A
Operating power • at AC-1 — at 400 V rated value • at AC-3 — at 400 V rated value • at AC-4 at 400 V rated value	10 kW 4 kW 1 150 W
Control circuit/ Control	
Type of voltage of the control supply voltage	DC
Control supply voltage at DC • rated value	24 V
Control version of the switch operating mechanism	conventional
Auxiliary circuit	
Number of NC contacts for auxiliary contacts • instantaneous contact	0
Number of NO contacts for auxiliary contacts • instantaneous contact	1
Installation/ mounting/ dimensions	
Mounting type • Side-by-side mounting	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022 Yes
Height	48 mm
Width	45 mm
Depth	68 mm
Connections/Terminals	
Type of electrical connection • for main current circuit • for auxiliary and control current circuit	screw-type terminals screw-type terminals
Certificates/approvals	

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity
--------------------------	---------------------------------------	---------------------------



[Type Examination Certificate](#)



Test Certificates	Marine / Shipping	other
-------------------	-------------------	-------

[Special Test Certificate](#)

[Miscellaneous](#)

[Type Test Certificates/Test Report](#)



[Miscellaneous](#)

other

[Environmental Confirmations](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TF2010-0BB4>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TF2010-0BB4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TF2010-0BB4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TF2010-0BB4&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3TF2010-0BB4/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3TF2010-0BB4&objecttype=14&gridview=view1>

last modified:

12/13/2018