

Contactor, Size 00, 3-pole, AC-3 4 kW/400 V, Soldering pin connection Auxiliary switch 10E (1 NO) 230 V AC 50/60 Hz AC operation screw mounting (diagonal)



Figure similar

|                                          |                     |
|------------------------------------------|---------------------|
| Product designation                      | Miniature contactor |
| Product type designation                 | 3TF2                |
| General technical data                   |                     |
| Size of contactor                        | 0                   |
| Protection class IP                      |                     |
| • on the front                           | IP00                |
| Reference code acc. to DIN EN 81346-2    | Q                   |
| Ambient conditions                       |                     |
| Ambient temperature                      |                     |
| • during operation                       | -25 ... +55 °C      |
| Main circuit                             |                     |
| Number of poles for main current circuit | 3                   |
| Number of NO contacts for main contacts  | 3                   |
| Number of NC contacts for main contacts  | 0                   |
| Operating current                        |                     |
| • at AC-3                                |                     |

|                                                          |                       |
|----------------------------------------------------------|-----------------------|
| — at 400 V rated value                                   | 9 A                   |
| • at AC-4 at 400 V rated value                           | 2.6 A                 |
| <b>Operating power</b>                                   |                       |
| • at AC-1                                                |                       |
| — at 400 V rated value                                   | 10 kW                 |
| • at AC-3                                                |                       |
| — at 400 V rated value                                   | 4 kW                  |
| • at AC-4 at 400 V rated value                           | 1 150 W               |
| <b>Control circuit/ Control</b>                          |                       |
| <b>Type of voltage of the control supply voltage</b>     | AC                    |
| <b>Control supply voltage at AC</b>                      |                       |
| • at 50 Hz rated value                                   | 230 V                 |
| • at 60 Hz rated value                                   | 230 V                 |
| <b>Control version of the switch operating mechanism</b> | conventional          |
| <b>Auxiliary circuit</b>                                 |                       |
| <b>Number of NC contacts for auxiliary contacts</b>      |                       |
| • instantaneous contact                                  | 0                     |
| <b>Number of NO contacts for auxiliary contacts</b>      |                       |
| • instantaneous contact                                  | 1                     |
| <b>Installation/ mounting/ dimensions</b>                |                       |
| <b>Mounting type</b>                                     | screw fixing          |
| • Side-by-side mounting                                  | Yes                   |
| <b>Height</b>                                            | 36 mm                 |
| <b>Width</b>                                             | 50 mm                 |
| <b>Depth</b>                                             | 63 mm                 |
| <b>Connections/Terminals</b>                             |                       |
| <b>Type of electrical connection</b>                     |                       |
| • for main current circuit                               | solder pin connectors |
| • for auxiliary and control current circuit              | solder pin connectors |
| <b>Certificates/approvals</b>                            |                       |

| General Product Approval                                                          |                                                                                   |                                                                                   | Functional Safety/Safety of Machinery        | Declaration of Conformity                                                           | Test Certificates                        |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|----------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------|
|  |  |  | <a href="#">Type Examination Certificate</a> |  | <a href="#">Special Test Certificate</a> |
| CCC                                                                               | CSA                                                                               |                                                                                   |                                              | EG-Konf.                                                                            |                                          |

| Test Certificates             | Marine / Shipping                                  |                                                                                   | other                                       |                              |
|-------------------------------|----------------------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------|------------------------------|
| <a href="#">Miscellaneous</a> | <a href="#">Type Test Certificates/Test Report</a> |  | <a href="#">Environmental Confirmations</a> | <a href="#">Confirmation</a> |
|                               |                                                    | RMRS                                                                              |                                             |                              |

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TF2010-6AL2>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TF2010-6AL2>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TF2010-6AL2>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3TF2010-6AL2&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TF2010-6AL2&lang=en)

##### Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3TF2010-6AL2/char>

##### Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3TF2010-6AL2&objecttype=14&gridview=view1>

last modified:

12/13/2018