

Contactor, Size 00, 3-pole, AC-3 2.2 kW/400 V, screw terminal  
Auxiliary switch 01E (1 NC) 230 V AC 50 Hz, 277 V 60 Hz AC  
operation



Figure similar

|                                          |                     |
|------------------------------------------|---------------------|
| Product designation                      | Miniature contactor |
| Product type designation                 | 3TF2                |
| General technical data                   |                     |
| Size of contactor                        | 0                   |
| Protection class IP                      |                     |
| • on the front                           | IP20                |
| Reference code acc. to DIN EN 81346-2    | Q                   |
| Ambient conditions                       |                     |
| Ambient temperature                      |                     |
| • during operation                       | -25 ... +55 °C      |
| Main circuit                             |                     |
| Number of poles for main current circuit | 3                   |
| Number of NO contacts for main contacts  | 3                   |
| Number of NC contacts for main contacts  | 0                   |
| Operating current                        |                     |
| • at AC-3                                |                     |

|                                                          |                                                                                        |
|----------------------------------------------------------|----------------------------------------------------------------------------------------|
| — at 400 V rated value                                   | 5 A                                                                                    |
| • at AC-4 at 400 V rated value                           | 1.9 A                                                                                  |
| <b>Operating power</b>                                   |                                                                                        |
| • at AC-1                                                |                                                                                        |
| — at 400 V rated value                                   | 10 kW                                                                                  |
| • at AC-3                                                |                                                                                        |
| — at 400 V rated value                                   | 2.2 kW                                                                                 |
| • at AC-4 at 400 V rated value                           | 850 W                                                                                  |
| <b>Control circuit/ Control</b>                          |                                                                                        |
| <b>Type of voltage of the control supply voltage</b>     | AC                                                                                     |
| <b>Control supply voltage at AC</b>                      |                                                                                        |
| • at 50 Hz rated value                                   | 230 V                                                                                  |
| • at 60 Hz rated value                                   | 277 V                                                                                  |
| <b>Control version of the switch operating mechanism</b> | conventional                                                                           |
| <b>Auxiliary circuit</b>                                 |                                                                                        |
| <b>Number of NC contacts for auxiliary contacts</b>      |                                                                                        |
| • instantaneous contact                                  | 1                                                                                      |
| <b>Number of NO contacts for auxiliary contacts</b>      |                                                                                        |
| • instantaneous contact                                  | 0                                                                                      |
| <b>Installation/ mounting/ dimensions</b>                |                                                                                        |
| <b>Mounting type</b>                                     | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022 |
| • Side-by-side mounting                                  | Yes                                                                                    |
| <b>Height</b>                                            | 48 mm                                                                                  |
| <b>Width</b>                                             | 45 mm                                                                                  |
| <b>Depth</b>                                             | 68 mm                                                                                  |
| <b>Connections/Terminals</b>                             |                                                                                        |
| <b>Type of electrical connection</b>                     |                                                                                        |
| • for main current circuit                               | screw-type terminals                                                                   |
| • for auxiliary and control current circuit              | screw-type terminals                                                                   |
| <b>Certificates/approvals</b>                            |                                                                                        |

|                          |                                       |                           |
|--------------------------|---------------------------------------|---------------------------|
| General Product Approval | Functional Safety/Safety of Machinery | Declaration of Conformity |
|--------------------------|---------------------------------------|---------------------------|



[Type Examination Certificate](#)



|                   |                    |       |
|-------------------|--------------------|-------|
| Test Certificates | Marine / Ship-ping | other |
|-------------------|--------------------|-------|

[Special Test Certificate](#)

[Miscellaneous](#)

[Type Test Certificates/Test Report](#)



[Environmental Confirmations](#)

[Confirmation](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TF2801-0AP0>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TF2801-0AP0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TF2801-0AP0>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3TF2801-0AP0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TF2801-0AP0&lang=en)

### Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3TF2801-0AP0/char>

### Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3TF2801-0AP0&objecttype=14&gridview=view1>

last modified:

12/13/2018