

Contactor, Size 14, 3-pole, AC-3, 335kW, 400/380 V (690 V)
 Auxiliary switch 33 (3NO+3NC) Rectifier bridge built-in with reversing
 contactor 3TC44 AC operation 380 to 420 V AC 50/60 Hz

Product designation	Vacuum contactor
Product type designation	3TF6

General technical data

Size of contactor	14
Protection class IP	IP00
• on the front	
Reference code acc. to DIN EN 81346-2	Q

Ambient conditions

Ambient temperature	
• during operation	-25 ... +55 °C

Main circuit

Number of poles for main current circuit	3
Number of NO contacts for main contacts	3
Number of NC contacts for main contacts	0
Operating current	
• at AC-3	
— at 400 V rated value	630 A
• at AC-4 at 400 V rated value	300 A
Operating power	
• at AC-1	
— at 400 V rated value	415 kW
• at AC-3	
— at 400 V rated value	335 kW
• at AC-4 at 400 V rated value	168 000 W

Control circuit/ Control

Type of voltage of the control supply voltage	AC
Control supply voltage at AC	
• at 50 Hz rated value	380 ... 420 V
• at 60 Hz rated value	380 ... 420 V
Control version of the switch operating mechanism	conventional

Auxiliary circuit

Number of NC contacts for auxiliary contacts	
• instantaneous contact	3

Number of NO contacts for auxiliary contacts	
• instantaneous contact	3

Installation/ mounting/ dimensions

Mounting type	screw fixing
• Side-by-side mounting	Yes
Height	232 mm
Width	230 mm
Depth	237 mm

Connections/Terminals

Type of electrical connection	
• for main current circuit	screw-type terminals
• for auxiliary and control current circuit	screw-type terminals

Certificates/approvals

General Product Approval	Functional Safety/Safety of Machinery
 CCC  CSA  UL  UR  EAC	Type Examination Certificate

Test Certificates	Marine / Shipping	other
Special Test Certificate Miscellaneous  BUREAU VERITAS  RMRS  DNV-GL		Environmental Confirmations

other
Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TF6833-1QV7>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TF6833-1QV7>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TF6833-1QV7>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TF6833-1QV7&lang=en

Characteristic: Tripping characteristics, I^2t , Let-through current
<https://support.industry.siemens.com/cs/ww/en/ps/3TF6833-1QV7/char>

Further characteristics (e.g. electrical endurance, switching frequency)
<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3TF6833-1QV7&objecttype=14&gridview=view1>

last modified:

12/19/2018