

Plug-in part T1/T2, L-N, rated voltage UN 240 V AC UC 335 V A.C., IIMP 12.5 kA, only for 5SD7413-2 (3) and 5SD7414-2 (3)



Model	
Product brand name	SENTRON
Design of the product	only for 5SD7413-2 (3) and 5SD7414-2 (3)
General technical data	
SPD classification / acc. to EN 61643-11 / Test Class II, Type 2	Yes
SPD classification / acc. to EN 61643-11 / Test Class I, Type 1	Yes
Suitability for use	5SD7412-2,5SD7412-3,5SD7413-2,5SD7413-3,5SD7414-2,5SD7414-3
Accessories	
accessories	Plug-in part T1/T2, only for 5SD7413-2 (3) and 5SD7414-2 (3)
Mechanical Design	
Net weight	135 g
Certificates	



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SD7418-3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SD7418-3>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SD7418-3

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>