

Type 3 surge arrester Requirement class D Rated voltage UN 24 V  
UC 34 V AC, 2-pole for 1-phase power supply



Figure similar

Article number

General data	
Standard	IEC 61643-11: 2011, EN 61643-11: 2012
Product designation	Surge protection device
SPD classification / acc. to EN 61643-11	
• Test Class I, Type 1	No
• Test Class II, Type 2	No
• Test Class III, Type 3	Yes
Number of SPD ports	1
Design of the product	Surge arrester
Design of pole	2
Designation of the protective paths	L-N, L-PE, N-PE, (L+)-(L-), (L+/L-)-PE
Mounting type	DIN rail NS 35
Material / of the enclosure	PA 6.6-FR
Size of surge arrester	1WM
Degree of pollution	2
Overvoltage category / acc. to IEC 61010-1	III
Protection class IP / at connection all terminals	IP20

Shock acceleration	30 gn
Vibrational acceleration / at 5 Hz ... 500 Hz / limited to 2,5 h / per axis	5 gn
Ambient temperature / during operation	-40 °C ... 80 °C
Ambient temperature / during storage and transport	-40 °C ... 80 °C
Relative humidity / during operation	5 % ... 95 %
Installation altitude / at height above sea level / maximum	2 000 m
Width	17.7 mm
Height	90 mm
Depth	70.9 mm
Net weight	76 g

#### Electrical data

Type of distribution system	TN-S
Operating voltage	24 V AC
Continuous operating voltage	
• maximum	34 V
• maximum	34 V
Load current	26 A (30 °C)
Protective conductor current	5 µA (27 V AC)
Apparent power consumption / maximum	30 mVA
Discharge current	
• at (8/20) µs	1 kA
Short-circuit rating (SCCR) / at 264 V	1.5 kA
Protection level	
• between L and N	0.25 kV
• between L and PE	0.65 kV
• between N and L	0.18 kV
• between N and PE	0.65 kV
• between PE and N and/or L	0.55 kV
Response time	
• between L and (PE)N	25 ns
• between N and PE	100 ns
Settable response factor / of trip current	1.6
Fuse protection type / at V-shaped connection	25 A (gG / B / C)
Insulation resistance (Riso)	5 MΩ

#### Connections/Terminals

Type of electrical connection	Screw terminal
Wire stripping length	8 mm
Tightening torque	0.75 ... 0.85
Wire stripping length	8 mm
Connectable conductor cross-section	

<ul style="list-style-type: none"> <li>• for finely stranded conductor</li> </ul>	0.2 ... 2.5
<ul style="list-style-type: none"> <li>• for rigid conductor</li> </ul>	0.2 ... 4
<ul style="list-style-type: none"> <li>• finely stranded</li> </ul>	0.2 ... 2.5
AWG number / as coded connectable conductor cross section	24 ... 12
Design of the thread / of the connection screw	M3
Signal design	Defect signaling contact

### Indicator/remote signaling

Switching function / of the remote-signaling contacts	N/C contact
Operating voltage / of the remote-signaling contacts <ul style="list-style-type: none"> <li>• at AC</li> <li>• at DC</li> </ul>	250 ... 250 125 V (200 mA DC)
Operating current / of the remote-signaling contacts <ul style="list-style-type: none"> <li>• at AC</li> <li>• at DC</li> </ul>	3 mA ... 3 A 1 A DC (30 V DC)
Connection type of remote signaling contact	M3
Connectable conductor cross-section <ul style="list-style-type: none"> <li>• for remote signaling contacts / for rigid conductor</li> <li>• for finely stranded conductor / for remote signaling contacts</li> </ul>	0.2 ... 4 0.2 ... 2.5
Tightening torque / for remote signaling contacts	0.8 N·m
Wire stripping length / of the cable / for remote signaling contacts	8 mm

### NEMA/UL - Data

Type of distribution system	TN-S
TOV behavior <ul style="list-style-type: none"> <li>• at TOV test voltage</li> <li>• at TOV test voltage (L-N)</li> </ul>	50 V AC (120 min / withstand mode) 50 V AC (5 s / withstand mode) / 50 V AC (120 min / withstand mode)
Combustibility class acc. to UL 94	V0
AWG number / as coded connectable conductor cross section / according to UL / minimum	24
AWG number / as coded connectable conductor cross section / according to UL / maximum	12

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SD7432-4>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SD7432-4>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SD7432-4](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SD7432-4)

