

Surge arrester, Type 2, pluggable protective modules, UC 750V AC, 3-pole, for 4-wire networks (L1, L2, L3, pen), with remote signaling



Article number

General data	
Standard	IEC 61643-11: 2011, EN 61643-11: 2012
Product designation	Surge protection device
SPD classification / acc. to EN 61643-11	
• Test Class I, Type 1	No
• Test Class II, Type 2	Yes
• Test Class III, Type 3	No
Number of SPD ports	1
Design of the product	Surge arrester
Design of pole	3
Designation of the protective paths	L-PEN, L-PE
accessories	3 x 5SD7488-2
Mounting type	DIN rail NS 35
Material / of the enclosure	PA 6.6 / PBT
Degree of pollution	2
Overvoltage category / acc. to IEC 61010-1	III
Protection class IP / at connection all terminals	IP20
Shock acceleration	25 gn

Vibrational acceleration / at 5 Hz ... 500 Hz / limited to 2,5 h / per axis	5 gn
Ambient temperature / during operation	-40 °C ... 80 °C
Ambient temperature / during storage and transport	-40 °C ... 80 °C
Relative humidity / during operation	5 % ... 95 %
Installation altitude / at height above sea level / maximum	2 000 m
Width	53.4 mm
Height	99 mm
Depth	71.5 mm
Net weight	355 g

### Electrical data

Type of distribution system	TN-C, IT
Operating voltage	554 / 960 V AC ...90 V AC (IT)
Continuous operating voltage	
• maximum	760 V
Load current	80 A
Protective conductor current	1.5 mA (760 V AC)
Apparent power consumption / maximum	1 200 mVA
Discharge current	
• at (8/20) µs	15 kA
• 1 phase / at (8/20) µs	30 kA
Short-circuit rating (SCCR) / at 264 V	25 kA
Protection level	
• maximum	2.9 kV
Residual voltage	
• at rated value of discharge current / maximum	2.9 kV
• at 10 kA maximum	2.7 kV
• at 5 kA maximum	2.5 kV
• at 3 kA / maximum	2.3 kV
Response time	25 ns
Settable response factor / of trip current	1.6
Fuse protection type / at V-shaped connection	80 A AC (gG)
Fuse protection type / for T-connector	100 A AC (gG)

### Connections/Terminals

Type of electrical connection	Screw terminal
Wire stripping length	16 mm
Tightening torque	4.3 ... 4.7
Wire stripping length	16 mm
Connectable conductor cross-section	
• for finely stranded conductor	1.5 ... 25
• for rigid conductor	1.5 ... 35

AWG number / as coded connectable conductor cross section	15 ... 2
Design of the thread / of the connection screw	M5
Signal design	Optical, remote signaling contact

### Indicator/remote signaling

Switching function / of the remote-signaling contacts	PDT contact
Operating voltage / of the remote-signaling contacts <ul style="list-style-type: none"> <li>• at AC</li> <li>• at DC</li> </ul>	5 ... 250 30 V
Operating current / of the remote-signaling contacts <ul style="list-style-type: none"> <li>• at AC</li> <li>• at DC</li> </ul>	5 mA ... 1.5 A 1 A DC (30 V DC)
Connection type of remote signaling contact	M2
Connectable conductor cross-section <ul style="list-style-type: none"> <li>• for remote signaling contacts / for rigid conductor</li> <li>• for finely stranded conductor / for remote signaling contacts</li> </ul>	0.14 ... 1.5 0.14 ... 1.5
AWG number / as coded connectable conductor cross section / for remote signaling contacts / minimum	28
AWG number / as coded connectable conductor cross section / for remote signaling contacts / maximum	16
Tightening torque / for remote signaling contacts	0.25 N·m
Wire stripping length / of the cable / for remote signaling contacts	7 mm

### NEMA/UL - Data

Type of surge protective device (SPD) / according to UL	Type 4 SPD for Type 2 applications
Type of distribution system / according to UL	3D
Type of distribution system	TN-C, IT
Designation of the protective paths / according to UL	L-L, L-G
TOV behavior <ul style="list-style-type: none"> <li>• at TOV test voltage</li> </ul>	1000 V AC (5 s / withstand mode)
Measured Limiting Voltage (MLV) / between L and L	4 kV
Measured Limiting Voltage (MLV) / between L and Ground (GND)	2.5 kV
Maximum Continuous Operating Voltage (MCOV) / between L and Ground (GND)	750 V
Leakage current / according to UL	10 kA
AWG number / as coded connectable conductor cross section / for remote signaling contacts / according to UL / minimum	30

AWG number / as coded connectable conductor cross section / for remote signaling contacts / according to UL / maximum	14
Installation altitude above sea level / according to UL	6 562 ft
Gross weight [lb] / according to UL	0.86 lb
Net weight [lb] / according to UL	0.78 lb
Combustibility class acc. to UL 94	V0
Operating voltage / of the remote-signaling contacts / according to UL	125 V
Operating current / of the remote-signaling contacts / at AC / according to UL	1 A
AWG number / as coded connectable conductor cross section / according to UL / minimum	10
AWG number / as coded connectable conductor cross section / according to UL / maximum	2

#### Further information

##### **Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

##### **Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5SD7483-5>

##### **Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5SD7483-5>

##### **Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=5SD7483-5](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5SD7483-5)

##### **CAX-Online-Generator**

<http://www.siemens.com/cax>