

SIPLUS S7-1200 CPU 1214C AC/DC/relay -40...+70 °C with conformal coating based on 6ES7214-1BG40-0XB0 . compact CPU, AC/DC/relay, onboard I/O: 14 DI 24 V DC 10 DO relay 2 A 2 AI 0-10 V DC, Power supply: AC 85-264 V AC @ 47-63 Hz, Program/data memory 100 KB



General information	
Product type designation	CPU 1214C AC/DC/relay
Firmware version	V4.1
Engineering with	
<ul style="list-style-type: none"> <li>Programming package</li> </ul>	STEP 7 V13 or higher
Supply voltage	
Rated value (AC)	
<ul style="list-style-type: none"> <li>120 V AC</li> </ul>	Yes
<ul style="list-style-type: none"> <li>230 V AC</li> </ul>	Yes
permissible range, lower limit (AC)	85 V
permissible range, upper limit (AC)	264 V
Line frequency	
<ul style="list-style-type: none"> <li>permissible range, lower limit</li> </ul>	47 Hz
<ul style="list-style-type: none"> <li>permissible range, upper limit</li> </ul>	63 Hz
Input current	
Current consumption (rated value)	100 mA at 120 V AC; 50 mA at 240 V AC
Current consumption, max.	300 mA at 120 V AC; 150 mA at 240 V AC
Inrush current, max.	20 A; at 264 V

<b>Output current</b>	
for backplane bus (5 V DC), max.	1 600 mA; Max. 5 V DC for SM and CM
<b>Encoder supply</b>	
24 V encoder supply	
• 24 V	20.4 to 28.8V
<b>Power loss</b>	
Power loss, typ.	14 W
<b>Memory</b>	
Work memory	
• integrated	100 kbyte
• expandable	No
Load memory	
• integrated	4 Mbyte
• Plug-in (SIMATIC Memory Card), max.	with SIMATIC memory card
Backup	
• present	Yes; maintenance-free
• without battery	Yes
<b>CPU processing times</b>	
for bit operations, typ.	0.085 µs; / instruction
for word operations, typ.	1.7 µs; / instruction
for floating point arithmetic, typ.	2.3 µs; / instruction
<b>CPU-blocks</b>	
Number of blocks (total)	DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used
OB	
• Number, max.	Limited only by RAM for code
<b>Data areas and their retentivity</b>	
Retentive data area (incl. timers, counters, flags), max.	10 kbyte
Flag	
• Number, max.	8 kbyte; Size of bit memory address area
<b>Address area</b>	
Process image	
• Inputs, adjustable	1 kbyte
• Outputs, adjustable	1 kbyte
<b>Hardware configuration</b>	
Number of modules per system, max.	3 communication modules, no signal board can be used, 8 signal modules

Time of day	
<b>Clock</b>	
<ul style="list-style-type: none"> <li>• Hardware clock (real-time)</li> <li>• Backup time</li> <li>• Deviation per day, max.</li> </ul>	Yes 480 h; Typical 60 s/month at 25 °C
Digital inputs	
Number of digital inputs	14; Integrated
<ul style="list-style-type: none"> <li>• of which inputs usable for technological functions</li> </ul>	6; HSC (High Speed Counting)
Source/sink input	Yes
<b>Number of simultaneously controllable inputs</b>	
all mounting positions	
— up to 40 °C, max.	14
<b>Input voltage</b>	
<ul style="list-style-type: none"> <li>• Rated value (DC)</li> <li>• for signal "0"</li> <li>• for signal "1"</li> </ul>	24 V 5 V DC at 1 mA 15 V DC at 2.5 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— parameterizable	0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
— at "0" to "1", min.	0.2 ms
— at "0" to "1", max.	12.8 ms
for interrupt inputs	
— parameterizable	Yes
for technological functions	
— parameterizable	Yes; Single phase : 3 at 100 kHz & 3 at 30 kHz, differential: 3 at 80 kHz & 3 at 30 kHz
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> <li>• unshielded, max.</li> </ul>	500 m; 50 m for technological functions 300 m; For technological functions: No
Digital outputs	
Number of digital outputs	10; Relays
<b>Switching capacity of the outputs</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> <li>• on lamp load, max.</li> </ul>	2 A 30 W with DC, 200 W with AC
<b>Output delay with resistive load</b>	
<ul style="list-style-type: none"> <li>• "0" to "1", max.</li> <li>• "1" to "0", max.</li> </ul>	10 ms; max. 10 ms; max.
<b>Switching frequency</b>	
<ul style="list-style-type: none"> <li>• of the pulse outputs, with resistive load, max.</li> </ul>	1 Hz
<b>Relay outputs</b>	

• Number of relay outputs	10
• Number of operating cycles, max.	mechanically 10 million, at rated load voltage 100 000
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	150 m
<b>Analog inputs</b>	
Number of analog inputs	2
<b>Input ranges</b>	
• Voltage	Yes
<b>Input ranges (rated values), voltages</b>	
• 0 to +10 V	Yes
• Input resistance (0 to 10 V)	≥100k ohms
<b>Cable length</b>	
• shielded, max.	100 m; twisted and shielded
<b>Analog outputs</b>	
Number of analog outputs	0
<b>Analog value generation for the inputs</b>	
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	10 bit
• Integration time, parameterizable	Yes
• Conversion time (per channel)	625 μs
<b>Encoder</b>	
<b>Connectable encoders</b>	
• 2-wire sensor	Yes
<b>1. Interface</b>	
Interface type	PROFINET
Physics	Ethernet
Isolated	Yes
automatic detection of transmission rate	Yes
Autonegotiation	Yes
Autocrossing	Yes
<b>Protocols</b>	
• PROFINET IO Controller	Yes
• PROFINET IO Device	Yes; Also simultaneously with IO-Device functionality
<b>PROFINET IO Controller</b>	
• Transmission rate, max.	100 Mbit/s
<b>Services</b>	
— Number of connectable IO Devices, max.	16
<b>PROFINET IO Device</b>	

Services	
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2

### Protocols

Supports protocol for PROFINET IO	Yes
PROFIBUS	Yes; CM 1243-5 required
AS-Interface	Yes

### Protocols (Ethernet)

• TCP/IP	Yes
----------	-----

### Open IE communication

• TCP/IP	Yes
• ISO-on-TCP (RFC1006)	Yes
• UDP	Yes

### Web server

• supported	Yes
• User-defined websites	Yes

### Further protocols

• MODBUS	Yes
----------	-----

### Communication functions

#### S7 communication

• supported	Yes
• as server	Yes
• as client	Yes

#### Number of connections

• overall	16; dynamically
-----------	-----------------

### Test commissioning functions

#### Status/control

• Status/control variable	Yes
• Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters

#### Forcing

• Forcing	Yes
-----------	-----

#### Diagnostic buffer

• present	Yes
-----------	-----

#### Traces

• Number of configurable Traces	2; Up to 512 KB of data per trace are possible
---------------------------------	--

### Integrated Functions

Number of counters	6
Counting frequency (counter) max.	100 kHz
Frequency measurement	Yes

controlled positioning	Yes
PID controller	Yes
Number of alarm inputs	4

### Potential separation

Potential separation digital inputs	
<ul style="list-style-type: none"> <li>Potential separation digital inputs</li> <li>between the channels, in groups of</li> </ul>	500V AC for 1 minute 1
Potential separation digital outputs	
<ul style="list-style-type: none"> <li>Potential separation digital outputs</li> <li>between the channels</li> <li>between the channels, in groups of</li> </ul>	Relays No 2

### EMC

Interference immunity against discharge of static electricity	
<ul style="list-style-type: none"> <li>Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 <ul style="list-style-type: none"> <li>Test voltage at air discharge</li> <li>Test voltage at contact discharge</li> </ul> </li> </ul>	Yes 8 kV 6 kV
Interference immunity to cable-borne interference	
<ul style="list-style-type: none"> <li>Interference immunity on supply lines acc. to IEC 61000-4-4</li> <li>Interference immunity on signal cables acc. to IEC 61000-4-4</li> </ul>	Yes Yes
Interference immunity against voltage surge	
<ul style="list-style-type: none"> <li>on the supply lines acc. to IEC 61000-4-5</li> </ul>	Yes
Interference immunity against conducted variable disturbance induced by high-frequency fields	
<ul style="list-style-type: none"> <li>Interference immunity against high-frequency radiation acc. to IEC 61000-4-6</li> </ul>	Yes
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> <li>Limit class A, for use in industrial areas</li> <li>Limit class B, for use in residential areas</li> </ul>	Yes; Group 1 Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011

### Degree and class of protection

Degree of protection acc. to EN 60529	
<ul style="list-style-type: none"> <li>IP20</li> </ul>	Yes

### Standards, approvals, certificates

CE mark	Yes
---------	-----

### Ambient conditions

Free fall	
<ul style="list-style-type: none"> <li>Fall height, max.</li> </ul>	0.3 m; five times, in product package
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>min.</li> </ul>	-40 °C; = Tmin; Startup @ -25 °C

<ul style="list-style-type: none"> <li>• max.</li> </ul>	70 °C; = Tmax; Tmax > +55 °C number of simultaneously switched-on digital inputs 7, digital outputs 5, analog inputs 2 (no adjacent points) with horizontal mounting position; Tmax > +60 °C number of simultaneously switched-on digital inputs 7, digital outputs 5, analog inputs 1 (no adjacent points) with horizontal mounting position
<b>Ambient temperature during storage/transportation</b>	
<ul style="list-style-type: none"> <li>• min.</li> </ul>	-40 °C
<ul style="list-style-type: none"> <li>• max.</li> </ul>	70 °C
<b>Altitude during operation relating to sea level</b>	
<ul style="list-style-type: none"> <li>• Installation altitude above sea level, max.</li> </ul>	2 000 m
<ul style="list-style-type: none"> <li>• Ambient air temperature-barometric pressure-altitude</li> </ul>	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m); above 2 000 m max. 132 V AC
<b>Relative humidity</b>	
<ul style="list-style-type: none"> <li>• With condensation, tested in accordance with IEC 60068-2-38, max.</li> </ul>	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
<b>Vibrations</b>	
<ul style="list-style-type: none"> <li>• Vibration resistance during operation acc. to IEC 60068-2-6</li> </ul>	2 g (m/s <sup>2</sup> ) wall mounting, 1 g (m/s <sup>2</sup> ) DIN rail
<ul style="list-style-type: none"> <li>• Operation, tested according to IEC 60068-2-6</li> </ul>	Yes
<b>Shock testing</b>	
<ul style="list-style-type: none"> <li>• tested according to IEC 60068-2-27</li> </ul>	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms
<b>Resistance</b>	
<b>Coolants and lubricants</b>	
<ul style="list-style-type: none"> <li>— Resistant to commercially available coolants and lubricants</li> </ul>	Yes
<b>Use in stationary industrial systems</b>	
<ul style="list-style-type: none"> <li>— to biologically active substances according to EN 60721-3-3</li> </ul>	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
<ul style="list-style-type: none"> <li>— to chemically active substances according to EN 60721-3-3</li> </ul>	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
<ul style="list-style-type: none"> <li>— to mechanically active substances according to EN 60721-3-3</li> </ul>	Yes; Class 3S4 incl. sand, dust, *
<b>Use on ships/at sea</b>	
<ul style="list-style-type: none"> <li>— to biologically active substances according to EN 60721-3-6</li> </ul>	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
<ul style="list-style-type: none"> <li>— to chemically active substances according to EN 60721-3-6</li> </ul>	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
<ul style="list-style-type: none"> <li>— to mechanically active substances according to EN 60721-3-6</li> </ul>	Yes; Class 6S3 incl. sand, dust; *
<b>Remark</b>	

— Note regarding classification of environmental conditions acc. to EN 60721

\* The supplied plug covers must remain in place over the unused interfaces during operation!

## Configuration

### Programming

#### Programming language

— LAD	Yes
— FBD	Yes
— SCL	Yes

### Cycle time monitoring

• adjustable	Yes
--------------	-----

## Dimensions

Width	110 mm
Height	100 mm
Depth	75 mm

## Weights

Weight, approx.	455 g
-----------------	-------

**last modified:** 07/29/2018