

SIPLUS LOGO! POWER 24V 1.3A
 SIPLUS LOGO! Power 24V 1,3A for medial stress -40...+70°C
 startup at -25°C based-on 6EP3331-6SB00-0AY0 . stabilized power
 supply input: AC 100-240 V output: DC 24 V / 1,3 A



Figure similar

Input	
Input	1-phase AC or DC
Rated voltage value V_{in} rated	100 ... 240 V
Voltage range AC	85 ... 264 V
Input voltage	
• at DC	110 ... 300 V
Wide-range input	Yes
Mains buffering at I_{out} rated, min.	40 ms; at $V_{in} = 187$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
Input current	
• at rated input voltage 120 V	0.7 A
• at rated input voltage 230 V	0.35 A
Switch-on current limiting (+25 °C), max.	25 A
I^2t , max.	0.8 A ² ·s
Built-in incoming fuse	internal

Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 6 A characteristic B or from 2 A characteristic C
Output	
Output	Controlled, isolated DC voltage
Rated voltage V_{out} DC	24 V
Total tolerance, static \pm	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	200 mV
Residual ripple peak-peak, typ.	30 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	300 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	50 mV
Adjustment range	22.2 ... 26.4 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for output voltage OK
On/off behavior	No overshoot of V_{out} (soft start)
Startup delay, max.	0.5 s
Voltage rise, typ.	100 ms
Rated current value I_{out} rated	1.3 A
Current range	0 ... 1.3 A
• Note	+55 ... +70 °C: Derating 2%/K
Supplied active power typical	31.2 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2
Efficiency	
Efficiency at V_{out} rated, I_{out} rated, approx.	86 %
Power loss at V_{out} rated, I_{out} rated, approx.	5 W
Power loss [W] during no-load operation maximum	0.3 W
Closed-loop control	
Dynamic mains compensation (V_{in} rated ± 15 %), max.	0.2 %
Dynamic load smoothing (I_{out} : 10/90/10 %), $U_{out} \pm$ typ.	1 %
Load step setting time 10 to 90%, typ.	1 ms
Load step setting time 90 to 10%, typ.	1 ms
Protection and monitoring	
Output overvoltage protection	Yes, according to EN 60950-1
Current limitation, typ.	1.7 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Constant current characteristic

Enduring short circuit current RMS value	
<ul style="list-style-type: none"> • maximum 	1.7 A
Overcurrent overload capability in normal operation	overload capability 150% I _{out} rated typ. 200 ms
Overload/short-circuit indicator	-
measuring point for output current	50 mV = [^] 1.3 A
Overcurrent overload capability when switching on	150% I _{out} rated typ. 200 ms

Safety	
Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class II (without protective conductor)
CE mark	Yes
Degree of protection (EN 60529)	IP20

EMC	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	not applicable
Noise immunity	EN 61000-6-2

Operating data	
Ambient temperature	
<ul style="list-style-type: none"> • during operation — Note • during transport • during storage • on cold restart minimum 	-40 ... +70 °C with natural convection -40 ... +85 °C -40 ... +85 °C -25 °C
Relative humidity with condensation maximum	100 %; Relative humidity, incl. condensation/frost permitted (no commissioning under condensation conditions)
Resistance to biologically active substances conformity acc. to EN 60721-3-3	Yes; Yes; class 3B2 mold, fungal, sponge spores (except fauna); class 3B3 upon request
Resistance to chemically active substances conformity acc. to EN 60721-3-3	Yes; Yes; class 3C4 (RH < 75 %) incl. salt spray according to EN 60068-2-52 (severity 3); the supplied connector covers must remain on the interfaces that are not used during operation!
Resistance to mechanically active substances conformity acc. to EN 60721-3-3	Yes; Yes; class 3S4 incl. sand, dust; the supplied connector covers must remain on the interfaces that are not used during operation!

Mechanics	
Connection technology	screw-type terminals
Connections	
<ul style="list-style-type: none"> • Supply input • Output • Auxiliary 	L, N: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded +, -: 2 screw terminals each for 0.5 ... 2.5 mm ² -
Width of the enclosure	36 mm

Height of the enclosure	90 mm
Depth of the enclosure	53 mm
Required spacing	
• top	20 mm
• bottom	20 mm
• left	0 mm
• right	0 mm
Weight, approx.	0.12 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15, direct mounting in different mounting positions
MTBF at 40 °C	3 094 996 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)