

SITOP PSE202U NEC CLASS 2  
 SITOP PSE202U NEC Class 2 Redundancy module Input/output: 24 V DC suitable for decoupling two SITOP power supplies Output power restricted to 100 VA



Input	
Input	DC voltage
Supply voltage	
<ul style="list-style-type: none"> <li>at DC</li> </ul>	24 ... 24 V
Input voltage	
<ul style="list-style-type: none"> <li>at DC</li> </ul>	19 ... 29 V
Output	
Output	Controlled, isolated DC voltage
Rated voltage $V_{out DC}$	24 V
Output voltage	$V_{in}$ - approx. 0.5 V
Product function Output voltage adjustable	No
Status display	Green LED for "both input voltages > switching threshold"; red LED for "at least one input voltage < switching threshold" or "output switched off"
Signaling	Isolated relay contact (contact rating 6 A/42 V AC, 30 V DC, but max. 100 VA): Contact closed if one or both input voltages < switching threshold or output is switched off. Setting range of switching threshold 20 V $\pm$ 0.5 V to 25 V $\pm$ 0.5 V
Rated current value $I_{out rated}$	3.8 A

Current range	4.6 A
<ul style="list-style-type: none"> <li>Note</li> </ul>	Maximum aggregate current in the event of an error according to NEC class 2 limit 8 A

### Efficiency

Efficiency at Vout rated, Iout rated, approx.	94.8 %
Power loss at Vout rated, Iout rated, approx.	5 W
Power loss [W] during no-load operation maximum	2 W

### Safety

Galvanic isolation	yes, SELV acc. to EN 60950-1 (relay contact)
Protection class	Class III
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; UL-Recognized (UL 60950-1, NEC class 2), File E151273
Explosion protection	-
FM approval	-
CB approval	No
Marine approval	-
Degree of protection (EN 60529)	IP20

### EMC

Emitted interference	EN 55022 Class B
Noise immunity	EN 61000-6-2

### Operating data

Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>— Note</li> <li>during transport</li> <li>during storage</li> </ul>	-20 ... +70 °C with natural convection -40 ... +85 °C -40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

### Mechanics

Connection technology	screw-type terminals
Connections	
<ul style="list-style-type: none"> <li>Supply input</li> <li>Auxiliary</li> </ul>	Input, output and ground: removable screw terminal, each 1 x 0.5 ... 2.5 mm <sup>2</sup> single-core/finely stranded Relay contact: 2 screw terminals for 0.5 ... 2.5 mm <sup>2</sup> single-core/finely stranded
Width of the enclosure	30 mm
Height of the enclosure	80 mm
Depth of the enclosure	100 mm
Required spacing	
<ul style="list-style-type: none"> <li>top</li> <li>bottom</li> </ul>	50 mm 50 mm

<ul style="list-style-type: none"> <li>• left</li> <li>• right</li> </ul>	0 mm
	0 mm
Weight, approx.	0.125 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
Electrical accessories	Removable spring-type terminal 6EP1971-5BA00
MTBF at 40 °C	678 210 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)