

SITOP PSU100E 48 V/5 A
 SITOP PSU100E 48 V/5 A Stabilized power supply Input: 120 / 230
 V AC Output: 48 V/5 A DC



Input	
Input	1-phase AC
Supply voltage	
• 1 at AC Rated value	100 V
• 2 at AC Rated value	230 V
Input voltage	
• 1 at AC	85 ... 132 V
• 2 at AC	170 ... 264 V
Wide-range input	No
Mains buffering at lout rated, min.	30 ms; at $V_{in} = 120/230\text{ V}$
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
Input current	
• at rated input voltage 120 V	4.4 A
• at rated input voltage 230 V	2 A
Switch-on current limiting (+25 °C), max.	58 A
I^2t , max.	1.5 A ² ·s
Built-in incoming fuse	T 6.3 A (not accessible), soldered

Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 10 A characteristic C
Output	
Output	Controlled, isolated DC voltage
Rated voltage Vout DC	48 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.2 %
Static load balancing, approx.	0.5 %
Residual ripple peak-peak, max.	50 mV
Residual ripple peak-peak, typ.	30 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	150 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	100 mV
Adjustment range	48 ... 54 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer; max. 240 W
Status display	Green LED for 48 V OK
Signaling	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for 48 V OK
On/off behavior	Overshoot of Vout approx. 2 %
Startup delay, max.	1.5 s
Voltage rise, typ.	15 ms
Voltage increase time of the output voltage maximum	500 ms
Rated current value Iout rated	5 A
Current range	0 ... 5 A
• Note	+60 ... +70 °C: Derating 5%/K
Supplied active power typical	240 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2
Efficiency	
Efficiency at Vout rated, Iout rated, approx.	92 %
Power loss at Vout rated, Iout rated, approx.	12 W
Closed-loop control	
Dynamic mains compensation (Vin rated ±15 %), max.	0.3 %
Dynamic load smoothing (Iout: 10/90/10 %), Uout ± typ.	1 %
Load step setting time 10 to 90%, typ.	0.5 ms
Load step setting time 90 to 10%, typ.	0.5 ms
Setting time maximum	1 ms
Protection and monitoring	
Output overvoltage protection	< 60 V
Current limitation, typ.	5.3 A

Property of the output Short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
Enduring short circuit current RMS value	8.7 A
• typical	

Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current	3.5 mA 1 mA
• maximum	
• typical	
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
Explosion protection	-
FM approval	-
CB approval	No
Marine approval	-
Degree of protection (EN 60529)	IP20

EMC

Emitted interference	EN 61000-6-4
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

Operating data

Ambient temperature	-25 ... +70 °C with natural convection -40 ... +85 °C -40 ... +85 °C
• during operation	
— Note	
• during transport	
• during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

Mechanics

Connection technology	screw-type terminals
Connections	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded +, -: 2 screw terminals each for 0.5 ... 2.5 mm ² 13, 14 (alarm signal): 1 screw terminal each for 0.5 ... 2.5 mm ²
• Supply input	
• Output	
• Auxiliary	13, 14 (alarm signal): 1 screw terminal each for 0.5 ... 2.5 mm ²
Width of the enclosure	42 mm
Height of the enclosure	125 mm
Depth of the enclosure	125 mm
Required spacing	

<ul style="list-style-type: none"> • top • bottom • left • right 	<p>50 mm</p> <p>50 mm</p> <p>0 mm</p> <p>0 mm</p>
Weight, approx.	0.5 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
MTBF at 40 °C	1 050 000 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)