

SITOP PSU3800 24 V/30-40 A

SITOP PSU3800 24V/30-40A Stabilized power supplies Input: 3 400-500 V AC Output: 24 V/30-40 A DC optimized for battery charging



Input	
Input	3-phase AC
Rated voltage value $V_{in}$ rated	400 ... 500 V
Voltage range AC	320 ... 575 V
Wide-range input	Yes
Mains buffering at $I_{out}$ rated, min.	10 ms; at $V_{in} = 400$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	45 ... 65 Hz
Input current	
• at rated input voltage 400 V	2.1 A
• at rated input voltage 500 V	1.7 A
Switch-on current limiting (+25 °C), max.	13 A
$I^2t$ , max.	2.24 A <sup>2</sup> ·s
Protection in the mains power input (IEC 898)	Required: 3-pole connected miniature circuit breaker 10 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489)
Output	
Output	Controlled, isolated DC voltage

Rated voltage Vout DC	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.2 %
Residual ripple peak-peak, max.	100 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	240 mV
Adjustment range	24 ... 28 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer; max. 960 W
Status display	Green LED for 24 V OK
Signaling	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK"
On/off behavior	minimal overshoot (< 3 %)
Startup delay, max.	0.1 s
Voltage increase time of the output voltage maximum	100 ms
Rated current value Iout rated	40 A
Current range	0 ... 40 A
• Note	+60 ... +70 °C: Derating 5%/K
Supplied active power typical	960 W
Constant overload current	
• on short-circuiting during the start-up typical	48 A
Parallel switching for enhanced performance	Yes; switchable characteristic
Numbers of parallel switchable units for enhanced performance	2

### Efficiency

Efficiency at Vout rated, Iout rated, approx.	94 %
Power loss at Vout rated, Iout rated, approx.	66 W
Power loss [W] during no-load operation maximum	4 W

### Closed-loop control

Dynamic mains compensation (Vin rated ±15 %), max.	1 %
Dynamic load smoothing (Iout: 50/100/50 %), Uout ± typ.	3 %
Setting time maximum	10 ms

### Protection and monitoring

Output overvoltage protection	< 31.8 V
Current limitation, typ.	43 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Constant current characteristic approx. 44 A
Enduring short circuit current RMS value	
• typical	48 A
Overload/short-circuit indicator	LED yellow for "overload", LED red for "latching shutdown"

### Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U <sub>out</sub> acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current	
• maximum	1 mA
• typical	0.6 mA
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
Explosion protection	IECEX Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T4
FM approval	-
CB approval	Yes
Marine approval	-
Degree of protection (EN 60529)	IP20

## EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

## Operating data

Ambient temperature	
• during operation	-25 ... +70 °C
— Note	With natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

## Mechanics

Connection technology	screw-type terminals
Connections	
• Supply input	L1, L2, L3, PE: 1 screw terminal each for 0.5 ... 4 mm <sup>2</sup> single-core/finely stranded
• Output	+: 2 screw terminals each for 0.5 ... 16 mm <sup>2</sup> ; -: 3 screw terminals each for 0.5 ... 16 mm <sup>2</sup>
• Auxiliary	13, 14 (alarm signal), 15, 16 (Remote): 1 screw terminal each for 0.05 ... 2.5 mm <sup>2</sup>
Width of the enclosure	135 mm
Height of the enclosure	145 mm
Depth of the enclosure	150 mm
Required spacing	
• top	40 mm
• bottom	40 mm

<ul style="list-style-type: none"> <li>• left</li> <li>• right</li> </ul>	0 mm
	0 mm
Weight, approx.	3.3 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x15
Electrical accessories	Buffer module
Mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
MTBF at 40 °C	517 015 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)