

SIMATIC S7-400, digital output SM 422, isolated 32 DO; 24 V DC, 0.5 A



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	30 mA
from backplane bus 5 V DC, max.	200 mA
Power loss	
Power loss, typ.	4 W
Digital outputs	
Number of digital outputs	32
Limitation of inductive shutdown voltage to	-27 V
Switching capacity of the outputs	
• on lamp load, max.	5 W
Output voltage	

• for signal "1", min.	L+ (-0.3 V)
<b>Output current</b>	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	0.6 A
• for signal "0" residual current, max.	0.3 mA
<b>Switching frequency</b>	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
<b>Total current of the outputs (per group)</b>	
all mounting positions	
— up to 60 °C, max.	2 A; 8 adjacent outputs each
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	No
<b>Potential separation</b>	
Potential separation digital outputs	
• between the channels, in groups of	32
• between the channels and backplane bus	Yes
<b>Isolation</b>	
Isolation tested with	500 V DC
<b>Dimensions</b>	
Width	25 mm
Height	290 mm
Depth	210 mm
<b>Weights</b>	
Weight, approx.	600 g
<b>last modified:</b>	12/24/2018