

MLFB-Ordering data

6FX2001-3GB02



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Electrical data		Mechanical data	
Operating voltage Up	DC 5 V ± 10 %	Shaft diameter	6 mm
Max. power consumption without	150 mA	Shaft length	10 mm
Signal level	Sinusoidal 1 Vpp	Angular acceleration, max.	100000 rad/s <sup>2</sup>
Resolution	1024 S/R	Moment of inertia of rotor	0.00000145 kgm <sup>2</sup>
Accuracy	63 rad	Vibration (55...2000 Hz), max.	300
Phase relation signal A to B	90° ± 10 %	Friction torque (at 20°C), max.	0.01 Nm
		Starting torque (at 20°C), max.	0.01 Nm
		Net weight	0.3 kg
<b>Limit frequency type at</b>		<b>Max. admissible speed</b>	
-3 dB	>= 100 kHz	Electrical	17600 rpm
-6 dB	>= 200 kHz	Mechanical	12000 rpm
<b>Cable length</b>		<b>Load capacity</b>	
To the downstream electronics,	150 m	n = 6000 rpm	
<b>Ambient temp in operation</b>		- Axial	10 N
<b>Fixed installation of flange outlet or cable</b>		- Radial at shaft end	20 N
- At Up = 5V ± 10%	-40 ... 100 °C	n > 6000 rpm	
<b>Flexible cable</b>		- Axial	40 N
- At Up = 5V ± 10%	-10 ... 100 °C	- Radial at shaft end	60 N
<b>Standards</b>		<b>Shock, max.</b>	
Compliance with standards	CE, cULus	2 ms	2000 m/s <sup>2</sup>
EMC class filter	Tested according to the EMC guidelines 89/336/EEC and the rules of the EMC guidelines (generic standards)	6 ms	1000 m/s <sup>2</sup>
		<b>Degree of protection</b>	
		Without shaft input	IP67
		With shaft input	IP64