

MLFB-Ordering data

6SE6430-2UD27-5CA0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.95
Number of phases	3 AC	Efficiency η	0.96
Line voltage	380 ... 480 V ± 10 %	Ambient conditions	
Line frequency	47 ... 63 Hz	Cooling	Fan
Rated current (LO)	17.30 A	Ambient temperature	
Output		Operation (LO)	-10 ... 40 °C
Number of phases	3 AC	Transport	-40 ... 70 °C
Rated voltage	480 V	Storage	-40 ... 70 °C
Rated power (LO)	7.50 kW / 10.00 hp		
Rated current (LO)	19.00 A		
Pulse frequency	4000 Hz		
Output frequency for V/f control	0 ... 650 Hz		

As a result of legal stipulations, a limit to 550 Hz is in production

Overload capability

Low Overload (LO)

140 % output current for 3 s, followed by 110 % output current for 57 s followed by 100 % output current for 240 s in a 300 s cycle time

MLFB-Ordering data

6SE6430-2UD27-5CA0



Figure similar

Mechanical data

Degree of protection IP20 / UL open type

Size FSC

Net weight 5.70 kg

Width 185.0 mm

Height 245.0 mm

Depth 195.0 mm

Inputs / outputs

Standard digital inputs

Number 6

Relay output

Number 3

Analog inputs

Number 2

Analog outputs

Number 2

PTC/ KTY interface

Number 1

Connections

Motor end

Conductor cross-section 10.00 mm²