



Figure similar

MLFB-Ordering data

6SL3210-5BB11-2UV1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																										
Input <table> <tr> <td>Number of phases</td><td>1 AC</td></tr> <tr> <td>Line voltage</td><td>200 ... 240 V -15 % +10 %</td></tr> <tr> <td>Line frequency</td><td>47 ... 63 Hz</td></tr> </table>	Number of phases	1 AC	Line voltage	200 ... 240 V -15 % +10 %	Line frequency	47 ... 63 Hz	<table> <tr> <td>Power factor λ</td><td>0.72</td></tr> <tr> <td>Offset factor $\cos \varphi$</td><td>0.95</td></tr> <tr> <td>Efficiency η</td><td>0.98</td></tr> </table>	Power factor λ	0.72	Offset factor $\cos \varphi$	0.95	Efficiency η	0.98														
Number of phases	1 AC																										
Line voltage	200 ... 240 V -15 % +10 %																										
Line frequency	47 ... 63 Hz																										
Power factor λ	0.72																										
Offset factor $\cos \varphi$	0.95																										
Efficiency η	0.98																										
Output <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Rated voltage</td><td>230 V</td></tr> <tr> <td>Rated power (HO)</td><td>0.12 kW / 0.16 hp</td></tr> <tr> <td>Rated power (LO)</td><td>0.12 kW / 0.12 hp</td></tr> <tr> <td>Rated current (HO)</td><td>0.90 A</td></tr> <tr> <td>Rated current (LO)</td><td>0.90 A</td></tr> <tr> <td>Pulse frequency</td><td>8.00 kHz</td></tr> <tr> <td>Output frequency</td><td>0 ... 550 Hz</td></tr> </table>	Number of phases	3 AC	Rated voltage	230 V	Rated power (HO)	0.12 kW / 0.16 hp	Rated power (LO)	0.12 kW / 0.12 hp	Rated current (HO)	0.90 A	Rated current (LO)	0.90 A	Pulse frequency	8.00 kHz	Output frequency	0 ... 550 Hz	Ambient conditions <table> <tr> <td>Cooling</td><td>convection cooling</td></tr> <tr> <td>Installation altitude</td><td>1000 m (3281 ft)</td></tr> </table> Ambient temperature <table> <tr> <td>Operation</td><td>-10 ... 60 °C (14 ... 140 °F)</td></tr> <tr> <td>Storage</td><td>-40 ... 70 °C (-40 ... 158 °F)</td></tr> </table> Relative humidity <table> <tr> <td>Max. operation</td><td>95 %</td></tr> </table>	Cooling	convection cooling	Installation altitude	1000 m (3281 ft)	Operation	-10 ... 60 °C (14 ... 140 °F)	Storage	-40 ... 70 °C (-40 ... 158 °F)	Max. operation	95 %
Number of phases	3 AC																										
Rated voltage	230 V																										
Rated power (HO)	0.12 kW / 0.16 hp																										
Rated power (LO)	0.12 kW / 0.12 hp																										
Rated current (HO)	0.90 A																										
Rated current (LO)	0.90 A																										
Pulse frequency	8.00 kHz																										
Output frequency	0 ... 550 Hz																										
Cooling	convection cooling																										
Installation altitude	1000 m (3281 ft)																										
Operation	-10 ... 60 °C (14 ... 140 °F)																										
Storage	-40 ... 70 °C (-40 ... 158 °F)																										
Max. operation	95 %																										
	Communication <table> <tr> <td>Communication</td><td>USS, Modbus RTU</td></tr> </table>	Communication	USS, Modbus RTU																								
Communication	USS, Modbus RTU																										
	Standards <table> <tr> <td>Compliance with standards</td><td>CE, cULus, C-Tick (RCM), KC</td></tr> <tr> <td>CE marking</td><td>EN 61800-5-1 /EN 60204-1 and EN 61800-3</td></tr> </table>	Compliance with standards	CE, cULus, C-Tick (RCM), KC	CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																						
Compliance with standards	CE, cULus, C-Tick (RCM), KC																										
CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																										

Overload capability

Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s

SIEMENS

Data sheet for SINAMICS V20

MLFB-Ordering data 6SL3210-5BB11-2UV1



Figure similar

Mechanical data		Connections	
Mounting position	Wall mounting / side-by-side mounting	Max. motor cable length	
Degree of protection	IP20 / UL open type	Shielded	25 m (82 ft)
Size	FSAA	Unshielded	50 m (164 ft)
Net weight	0.70 kg (1.54 lb)		
Width	68.0 mm (2.68 in)		
Height	142.0 mm (5.59 in)		
Depth	107.8 mm (4.24 in)		

Inputs / outputs	
Standard digital inputs	
Number	4
Digital outputs	
Number as relay changeover contact	1
Number as transistor	1
Analog inputs	
Number	2 (Can be used as additional digital input)
Analog outputs	
Number	1