

MLFB-Ordering data

6SL3210-5BB23-0AV0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																										
Input <table> <tr> <td>Number of phases</td><td>1 AC</td></tr> <tr> <td>Line voltage</td><td>200 ... 240 V -10 % +10 %</td></tr> <tr> <td>Line frequency</td><td>47 ... 63 Hz</td></tr> </table>	Number of phases	1 AC	Line voltage	200 ... 240 V -10 % +10 %	Line frequency	47 ... 63 Hz	<table> <tr> <td>Power factor λ</td><td>0.72</td></tr> <tr> <td>Offset factor $\cos \varphi$</td><td>0.95</td></tr> <tr> <td>Efficiency η</td><td>0.98</td></tr> </table>	Power factor λ	0.72	Offset factor $\cos \varphi$	0.95	Efficiency η	0.98														
Number of phases	1 AC																										
Line voltage	200 ... 240 V -10 % +10 %																										
Line frequency	47 ... 63 Hz																										
Power factor λ	0.72																										
Offset factor $\cos \varphi$	0.95																										
Efficiency η	0.98																										
Output <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Rated voltage</td><td>230 V</td></tr> <tr> <td>Rated power (HO)</td><td>3.00 kW / 4.00 hp</td></tr> <tr> <td>Rated power (LO)</td><td>3.00 kW / 4.00 hp</td></tr> <tr> <td>Rated current (HO)</td><td>13.60 A</td></tr> <tr> <td>Rated current (LO)</td><td>13.60 A</td></tr> <tr> <td>Pulse frequency</td><td>8.00 kHz</td></tr> <tr> <td>Output frequency</td><td>0 ... 550 Hz</td></tr> </table>	Number of phases	3 AC	Rated voltage	230 V	Rated power (HO)	3.00 kW / 4.00 hp	Rated power (LO)	3.00 kW / 4.00 hp	Rated current (HO)	13.60 A	Rated current (LO)	13.60 A	Pulse frequency	8.00 kHz	Output frequency	0 ... 550 Hz	Ambient conditions <table> <tr> <td>Cooling</td><td>External fan</td></tr> <tr> <td>Installation altitude</td><td>1000 m (3281 ft)</td></tr> </table> Ambient temperature <table> <tr> <td>Operation</td><td>-10 ... 60 °C (14 ... 140 °F)</td></tr> <tr> <td>Storage</td><td>-40 ... 70 °C (-40 ... 158 °F)</td></tr> </table> Relative humidity <table> <tr> <td>Max. operation</td><td>95 %</td></tr> </table>	Cooling	External fan	Installation altitude	1000 m (3281 ft)	Operation	-10 ... 60 °C (14 ... 140 °F)	Storage	-40 ... 70 °C (-40 ... 158 °F)	Max. operation	95 %
Number of phases	3 AC																										
Rated voltage	230 V																										
Rated power (HO)	3.00 kW / 4.00 hp																										
Rated power (LO)	3.00 kW / 4.00 hp																										
Rated current (HO)	13.60 A																										
Rated current (LO)	13.60 A																										
Pulse frequency	8.00 kHz																										
Output frequency	0 ... 550 Hz																										
Cooling	External fan																										
Installation altitude	1000 m (3281 ft)																										
Operation	-10 ... 60 °C (14 ... 140 °F)																										
Storage	-40 ... 70 °C (-40 ... 158 °F)																										
Max. operation	95 %																										
	Communication <table> <tr> <td>Communication</td><td>USS, Modbus RTU</td></tr> </table>	Communication	USS, Modbus RTU																								
Communication	USS, Modbus RTU																										
	Standards <table> <tr> <td>Compliance with standards</td><td>CE, cULus, C-Tick (RCM), KC</td></tr> <tr> <td>CE marking</td><td>EN 61800-5-1 /EN 60204-1 and EN 61800-3</td></tr> </table>	Compliance with standards	CE, cULus, C-Tick (RCM), KC	CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																						
Compliance with standards	CE, cULus, C-Tick (RCM), KC																										
CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																										

Overload capability

Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s

MLFB-Ordering data

6SL3210-5BB23-0AV0



Figure similar

Mechanical data

Mounting position	Through-hole mounting / wall mounting / side-by-side mounting
Degree of protection	IP20 / UL open type
Size	FSC
Net weight	2.50 kg (5.51 lb)
Width	184.0 mm (7.24 in)
Height	182.0 mm (7.17 in)
Depth	169.0 mm (6.65 in)

Connections

Max. motor cable length

Shielded	25 m (82 ft)
Unshielded	50 m (164 ft)

Inputs / outputs

Standard digital inputs

Number	4
--------	---

Digital outputs

Number as relay changeover contact	1
------------------------------------	---

Number as transistor	1
----------------------	---

Analog inputs

Number	2 (Can be used as additional digital input)
--------	---

Analog outputs

Number	1
--------	---