

Data manager for communication between PC U Configuration via web browser, reading out via web browser, APP (SmartPhone, tablet), CSV. and Powermanager, data memory

Model	
Product brand name	SETRON
Product designation	7KT PAC1200
Product type designation	Data manager

General technical data	
(measurement accuracy)	Total accuracy +/-1% (of full-scale value / class 1)
Measured variable current / rated value	63 A
Line frequency / rated value	Yes
• 50 Hz	
Measurable line frequency	50 +/- 5%
• Full-scale value	

Electricity	
Current / at output / rated value	5 A

Suitability	
<b>Suitability for use</b>	
• reactive power meter	
• revolution counter	
• Frequency meter	
• pulse counter	
• voltmeter	
• wattmeter	
Protocol / is supported	Modbus TCP

Measuring inputs	
Measurable supply voltage	230 V
• between (PE)N and L / at AC / maximum rated value	
• between the outer conductors / at AC / maximum rated value	400 V
(height)	85 mm
Depth	32.7 mm
Number of width units	4
(net weight)	280 g

Certificates	
--------------	--

## Declaration of Conformity



## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KT1260>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KT1260>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7KT1260](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KT1260)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>